

POS-615 POS System



CORE i3
Processor



True FLAT
PCAP Touch



Windows 10
IoT

Powered by the latest 6th generation Core i3 Processor. Delivers exceptional Performance & Power even in the most demanding applications.



Technical Specification

Model	POS-615B	POS-615C
CPU	Intel Baytrail J1900 QUAD CORE 2.00 GHz processor Embedded, Low Power, FANLESS processor, 2 MB Cache memory	Intel Core i3-6100T 3.20 GHz processor 3 MB Cache memory
Chipset	Intel Baytrail J1900 with Integrated Graphics chipset	Intel H110 Chipset
Operator Display		
Size	15-inch TFT LCD with LED Backlight, Anti-glare	
Maximum Resolution	1024 x 768	
Brightness	350 nits	
Touch Screen	Projected Capacitive Touch (PCAP) – True FLAT	
Memory		
Storage Memory	128 GB Solid State Disk (SSD) or 500 GB HDD	
System Memory	4 GB DDR3L RAM	4 GB DDR4 RAM
External Interface ports		
USB	5	
Serial (DB9)	3	4
Network	1 x Gigabit LAN	2 x Gigabit LAN
Display Port	1 x VGA	1 x HDMI
Audio	1 x Line-In, 1 x Line-out	
Factory options	Wi-Fi LAN module (Mini-PCIe)	
Environmental		
Operating Temperature	5°C ~40°C	
Storage Temperature	-20°C ~ 55°C	
Power Adapter	DC 12 V/5 A 60 W	
Optional Accessories		
Printer	High Speed POS Thermal printer, 76 mm paper, 260 mm/sec, auto-cutter (Serial+USB+LAN) interface	
Cash Drawer	4-Bill/8-Coin Metal Cash Drawer with Lock & Key and micro-switch	
MSR	3 Track-OPOS Compliant, USB interface	
Customer Display	10.4 inch Touch LCD (rear mounted) Display resolution: 800 x 600 or 20 x 2 Graphic LCD (rear mounted) or 20 x 2 Graphic LCD (Pole type)	
Mounting Options	VESA-compliant Wall Mount Kit	
Dimension (W X D X H) (without any accessories)	4º tilt angle :382 mm x 220 mm x 356 mm 84º tilt angle :382 mm x 294 mm x 300 mm	
Net Weight (without accessories)	6.1 kg (approx)	
Operating System		
Operating System supported (Both 32-bit &64-bit versions)	Windows 10 IOT Enterprise 2016 LTSB Entry Windows Embedded POSReady 7 Linux (subject to confirmation)	Windows 10 IOT Enterprise 2016 LTSB Value Windows Embedded POSReady 7 Linux (subject to confirmation)


Accessories



20 x 2 LCM
Customer Display



10.4" LCD
Customer Display



MSR

Form No. CAT-POS-615-060 R00

Essae-Teraoka Pvt. Ltd.

410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034
info@essae.com
http://www.essae.com

+91 80 3021 3021
+91 80 3021 3001
1-800-425-3111
0-78488 12346

Essae[®]
...for Excellence

Your Essae representative

▲ Factories in Bengaluru and Goa ▲ 45 Branch Offices ▲ 250+ Service engineers ▲ 350+ Resellers/Partners

Note : Specifications are subject to change without notice. Other names and logos used are property of respective brands.