

Delivering superior performance
with Outstanding durability

MP 280

2 inch Thermal Mobile Printer



INTRODUCTORY
OFFER

EXCLUSIVE CARRY CASE

Features

- Bluetooth V4.2 Connectivity with auto-reconnect
- Direct plugin - works without battery also
- Battery saver mode
- BIS Certified
- Rugged Design



C&F Receipts



Cafes



Supermarkets



Restaurants



Juice Shops



Grocery Shops



Toll Gates

MRP 11,500
shop now



BUY ☎ 1800 200 5123
SERVICE ☎ 1800 425 4566 /
3030 9797*

* Please prefix city STD code before dialling

TVS Electronics Limited
Arihant E-Park, 117/1, 8th & 9th Floor,
L.B.Road, Chennai - 600 020
www.tvs-e.in | Email:sales-support@tvs-e.in

MP280 Specification		Features
Print Characteristics		
Print Method	Direct Thermal	
Print Speed	up to 80 mm/s	
Print Resolution	203 dpi	
Print Width	Up to 48 mm	
Sensor	Paper End: Reflective Sensor	
	Paper Cover Open: Mechanical switch	
Media Characteristics		
Media Type	Receipt	
Media Width	58mm	
Media Roll Diameter	Up to 40 mm	
Media Thickness	60 to 100 µm	
Supply Method	Easy Paper Loading	
Physical Characteristics		
Dimension	85 x 115 x 46 (W x D x H)	
Weight	190 grams	
Battery	7.4 V, Li-ion, 2100 mAh, Rechargeable	
	Charging Time: Up to 2.10 hrs	
Performance Characteristics		
Memory	32KB SDRAM, 256 KB Flash ROM, Ext	
Interface Options	USB (CDC, HMSC), Bluetooth V4.2	
Environment Characteristics		
Operating Temperature	0 ~ 50°C, Humidity : 20 ~ 80% RH	
Storage Temperature	0 ~ 60°C, Humidity : 10 ~ 90% RH	
Software		
Emulation	Supports Standard ESC / POS Commands	
SDK	Android SDK	
Fonts / Graphics / Symbolizes		
Character Size	12x 24 dot font	
Characters Per Line	24 characters/line	
	32 characters/line	
	42 characters/line	
Character Sets	Alphanumeric: 95 Expanded Graphics:128 × 33 page	
Graphics	Supporting graphics, formats, layouts, and logos	
Barcode Symbolizes	EAN8, UPCA, CODE 39, CODE 128, ITF	
Accessories		
Standard	Battery Pack & Power adopter	
Optional	Printer External Art-leather Cover	

TVS Electronics Limited

Arihant E-Park, 117/1, 8th & 9th Floor,
L.B.Road, Chennai - 600 020
www.tvs-e.in | Email:sales-support@tvs-e.in

